



GSA ACRYLIC GAP FILLER

Description

A superior quality paintable gap filler for interior and exterior applications. For sealing and filling gaps and cracks where movement occurs, such as those between plasterboard, architraves and skirting boards. Displays excellent adhesion to concrete, masonry, wood, brick, ceramic tiles and plasterboard.

Key Performance Properties

Paintable, Water based, One Component, Flexible.

Application

Joints on window sills, between plinths and walls, between masonry, Joints with movement till max 10%, Filling of cracks in concrete and plasterwork

Specification Guide at 25°C

Tooling Time 30 minutes

Ready for painting 2 hours

Cure time 48 hours

Joint movement max 10%

These values may vary depending on environmental factors such as temperature, moisture, and type of substrates

Directions

Make sure surfaces are clean, dust and grease free. Cut the cartridge seal and screw on nozzle which should be cut to your required size. Using a caulking gun, apply sealant into the gap or joint ensuring a good solid fill. Smooth if required using a putty knife or wet sponge. Remove any excess immediately with a damp cloth. Sealant should be touch dry in approximately 30 minutes and can be painted over within 2 hours with emulsion paint. For oil-based paints allow 48 hours before painting. Paints that shrink during drying (some water-based undercoats and flat paints) may crack. Test paint on a small section of the sealant. Paint cracking can be reduced by applying vinyl or acrylic semi-gloss or oil-based undercoat first or allowing the sealant to fully cure before painting. After use, clean tools with water. Cured sealant can be trimmed with a knife.

Packaging

450 gram cartridge

Storage/Shelf Life

Store between 5°C and 25°C in cool dry conditions. Protect from low temperatures and frost. Shelf life 24 months for an unopened cartridge stored in a cool dry place.

Health & Safety

Non-hazardous product. Keep away from children and animals. Do not take internally, keep out of eyes. If contact with skin, wash with soap and water.

Limitations

Do not apply in wet or damp conditions, below 5°C or below ground level. Not recommended for joints where directly exposed to water or where water pools. Not suitable for fine joints in tongue and groove boards or weatherboard overlaps. Painting will improve exterior durability. To avoid paint cracking, apply only to gaps no larger than 5mm deep and 10mm wide.

First Aid

Please refer to the Safety Data Sheet which is available at www.cwbrands.com.au/





GSA Acrylic Gap Filler

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.