



GSA FAST FILLER

PRODUCT DESCRIPTION:

GSA Fast Filler is a ready to use lightweight, rapid setting filler for interior and exterior use. Easy to sand and clean up tools with water. Can be painted over with both water and solvent based paints

APPLICATIONS: Ideal for filling cracks, primed nail heads, small and large holes in plaster, plasterboard, wood and masonry.

SURFACE PREPARATION: Surface must be clean, dry and free of loose or protruding material - sand surface lightly if required. It is recommended to prime exterior timber surfaces appropriately before application.

DIRECTIONS: Apply a small amount of GSA fast filler onto a flexible filling blade. Apply in thin layers pressing firmly into the area being filled and remove any excess filler. Can be painted when set (30 mins) but expect longer drying times in cold or humid conditions. Sand with 120-180 grith sandpaper if a smooth finish is required. GSA fast filler can be primed with water or oil based primers prior to top coating.

PRECAUTIONS:

Use GSA Acrylic Gap Filler where movement occurs. If filling very large holes use GSA Builders Filler with a relevant filling agent. DO NOT use on metal, plastic or directly into exterior timbers as it is likely to swell or shrink on absorption of water. Avoid using below 5°C or wet conditions. Protect from rain until dry and painted over with 2 coats of appropriate paint. DO NOT NAIL.

PACK SIZE: 180g - GFF180 260g - GFF260

CLEAN UP: Clean tools and hands with warm soapy water. Uncured product may be removed with water. Cured product can be removed by scraping or sanding.

STORAGE: Close lid tightly after use. Store in a cool place out of direct sunlight. Shelf life: 12 months in an unopened container.

HEALTH & SAFETY: Safety Data Sheet available from www.cwbrands.com.au

Non-hazardous product **Keep Out Of Reach Of Children.** If swallowed seek medical advice immediately or contact the **Poisons Information Center on 13 11 26.**

DISPOSAL: Dispose of in accordance with local, state and federal regulations



GSA EASY SAND N FILL

Disclaimer

CW Brands Pty Ltd believes that the information in this technical data sheet is an accurate description of the typical uses of the product. The data and statements are based on our research and development work and is to the best of our knowledge true and accurate. The user must ensure of the product(s) in their application prior to use in particular to determine its performance, efficiency and safety. The use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Products conform solely to the information contained in this and other related CW Brands Pty Ltd publications.

CW Brands Pty Ltd reserves the right to make changes to specifications and information related to the products at any time. Users are asked to check that the literature in their possession is the latest issue. Statements contained herein should not be considered as a warranty of any kind, expressed or implied in describing the performance or suitability of the product for a particular application. No liability is accepted for infringement of any patents or any other intellectual property right.